

INSTALLS IN MINUTES • FLEXIBLE CEMENT MAT
 MEETS ALL ADA REQUIREMENTS • FINISHED LOW PROFILE EDGE
 BONDS TO ASPHALT





POWERBOND RAMP UP DETECTABLE WARNING MATS

GENERAL INFORMATION

DESCRIPTION:

ADA compliant truncated-dome tactile warning system for pavement. (ADA Accessibility Guidelines-ADAAG Section 4.29.2)

USES:

Use SSTD POWERBOND RAMP UP System where ADA requirements need to be met in an asphalt condition. The system may be installed directly over asphalt.

PRODUCT ATTRIBUTES:

This system is an ADA-compliant patterned mat with a high contrast, Low profile, slip resistant surface.

PRODUCT INFORMATION

SSTD POWERBOND RAMP UP MAT is a pre-molded tactile dome sheet composed of fiber-reinforced, polymer-modified flexible cement and coated with flexible, wear resistant, UV protective resins. Incorporated into the mat is our proprietary "POWERBOND" peel & stick technology. "POWERBOND" is a peel & stick with cold surface temperature range capabilities.

Mats are 2MM thick with truncated domes being 0.9 in. diameter by 0.2 in. high.

Sizes: 3' x 4', 3' x 5', 2' x 4', 2' x 5'.

Patterns: Inline (Square) Pattern - 1.67 in. on center each way.

Wide Inline (Square) Pattern - 2.35 in. on center each way.

Offset (Staggered) Pattern - 1.67 in. on center diagonally.

LIMITATIONS:

Do not apply in weather temperatures below 45 degrees Fahrenheit or when surface temperature is below 20 degrees Fahrenheit.

Protect both Powerbond Ramp Up Mat and perimeter adhesive from freezing. Do not cut Powerbond Ramp UP Mat into radius configuration (use SSTD Traditional mat for this).

Not for concrete applications.

SURFACE PREP AND INSTALLATION:

Please refer to SSTD POWERBOND RAMP UP installation guide, available for download via website or contact SafetyStepTD.

WARRANTY:

Five Year limited warranty available.

866.723.3883

1725 HOWARD PLACE - REDLANDS, CA 92373

WWW.SAFETYSTEPTD.COM